

MATERIAL SAFETY DATA SHEET
WEATHER-ALL (BC-WA)
6/23/05

SECTION I—MANUFACTURER

Crest Industries, Inc., 1337 King Road, Trenton, MI 48183 **Phone:** (734) 479-4141 **FAX:** (734) 479-4040
24 HOUR EMERGENCY TELEPHONE (CHEMTEL): (800) 255-3924 **INTERNATIONAL CALLS:** (813) 248-0585

SECTION II—PRODUCTS

HMIS RATING

H F R
1 0 0

Appearance and Odor
Milky white, baby powder

Solubility
% in Water
Rinsable

Solvent
Volume%
0

VOC Content
NONE

Flash
Point
°F °C
-NA-

Vapor Pres-
sure (mm Hg
at 20°C)
NA

Evap. Rate
(n-Butyl
Acetate=1)
NA

Boiling
Point
°F °C
212 100

Flammable
Limits in %
Lower Upper
-NA-

Autoig-
nitition Pt.
°F °C
-NA-

*Abbreviations: NA means Not Applicable.

SECTION III—HAZARDOUS INGREDIENTS

None

SECTION IV—PHYSICAL DATA

Evaporation Rate: Unknown **Vapor Density:** NA

Product Density (water=1): Less than 1

SECTION V—FIRE AND EXPLOSION DATA

Flammability Class: Non-flammable **Extinguishing Media:** NA

Special Fire Fighting Procedures: NA

Unusual Fire and Explosion Hazards: NA

SECTION VI—HEALTH HAZARD DATA

PRIMARY ROUTES OF EXPOSURE: Skin contact, Eye contact, Inhalation

SIGNS AND SYMPTOMS OF EXPOSURE:

INHALATION:

Acute Exposure: Irritation of the respiratory tract (nose, throat, lungs) possibly causing a burning sensation, runny nose, sore throat, coughing, chest discomfort (tightness).

Chronic Exposure: Unknown.

SKIN CONTACT:

Acute Exposure: Skin irritation

Chronic Exposure: Unknown

EYE CONTACT:

Acute Exposure: Irritation of the eyes with itching, burning, redness.

Chronic Exposure: Same as acute exposure

INGESTION:

Acute Exposure: Irritation to the mouth, and if swallowed, to the esophagus, stomach tissue and digestive tract.

Chronic Exposure: Unknown.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known to Crest Industries, Inc. but it is possible that eye, respiratory tract or skin diseases may be aggravated by overexposure.

CARCINOGENICITY: Products not listed by NTP, IARC or OSHA.

SECTION VII—EMERGENCY AND

FIRST AID PROCEDURES

INHALATION: Move to an area free from risk of further exposure. **EYE CONTACT:** Immediately flush with clean, lukewarm water (low pressure) for at least 15 minutes while lifting eyelids. Refer person to physician if irritation persists. **SKIN CONTACT:** Remove contaminated clothing immediately. Clean affected areas thoroughly with soap and water. Wash contaminated clothing thoroughly before reuse. Seek medical attention if irritation develops or persists. **INGESTION:** Induce vomiting. Consult physician, hospital emergency room or poison control center if illness results.

DISCLAIMER: The information contained in this MSDS is believed to be accurate and reliable as of the date indicated. **Crest Industries, Inc.** assumes no legal responsibility and makes no representation, warranty or guarantee, expressed or implied, as to the completeness or accuracy of the information. It is offered solely for your consideration, investigation and verification. The user is ultimately responsible for the safe use of the material in accordance with applicable federal, state, provincial and local laws and regulations.

SECTION VIII—EMPLOYEE PROTECTION
RECOMMENDATIONS

EYE PROTECTION: Wear safety glasses. **SKIN PROTECTION:**

Wear rubber gloves. **VENTILATION:** Local exhaust.

RESPIRATORY PROTECTION: None normally needed.

OTHER PROTECTIVE MEASURES: Eyewash stations should be available. Educate and train employees in safe use of the product. Follow all label instructions.

SECTION IX—REACTIVITY DATA

STABILITY: Stable under normal room conditions.

HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: By high heat and fire: carbon dioxide, carbon monoxide, silicon dioxide, smoke.

SECTION X—SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Prevent further spillage. Cover the spill with sawdust, vermiculite, Fuller's Earth or other absorbent material. Collect material and put in a container. Remove container to a safe place.

WASTE DISPOSAL METHOD: Follow all federal, state and local environmental control regulations. Incineration of the liquid or dried material is the preferred method. **RCRA STATUS:** NA

SECTION XI—SPECIAL PRECAUTIONS AND
STORAGE DATA

STORAGE TEMPERATURE

MINIMUM / MAXIMUM: 50°F (10°C) / 120°F (49°C)

RECOMMENDED SHELF LIFE: One year

PRECAUTIONS TO BE TAKEN IN HANDLING, STORAGE AND

USE: Do not store where it will freeze. Avoid all contact with eyes and excessive contact with skin. Wash hands after use and before eating, drinking, smoking or using the toilet. Employee education and training in the safe use and handling of this product is required under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

KEEP OUT OF THE REACH OF CHILDREN!

SECTION XII—EPA INFORMATION ON

HAZARDOUS INGREDIENTS

NA

SECTION XIII—CALIFORNIA PROPOSITION 65
WARNINGS

None

SECTION XIV—OZONE DEPLETION IN
THE UPPER ATMOSPHERE

This product does not contain upper atmosphere ozone depleting substances.